(REACH regulation (EC) n° 1907/2006 - n° 2015/830)



Version 7.1 (14-09-2015) - Page 1/8

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : FORK OIL EXP M 10W

1.2. Relevant identified uses of the substance or mixture and uses advised against

Fluid for fork

1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE Telephone : 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: .

Email : motul_hse@motul.fr

Registered company name (importer): High Performance Lubricants Ltd 21 O'Rorke Road, Penrose, Auckland 1061 PO Box 12 826 Penrose, Auckland, New Zealand 09 571 1366

1.4 24 HOUR EMERGENCY TEPLEPHONE NUMBER: 09 929 1483/0800 446 881 (toll free)

1.5 NATIONAL POISON LINE 0800 764 766

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation 9.1C

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

•	•
Hazard statements :	
H412	Harmful to aquatic life with long lasting effects.
Precautionary statem	nents - General:
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Precautionary statem	nents - Prevention:
P273	Avoid release to the environment.
Precautionary statem	nents - Disposal :
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

ECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS			
3 2 Mixiures Identification	(EC) 1272/2008	Note	%
Compexition9:474-00-6		L	25 <= x % < 50
CAS: 64742-65-0			
EC: 265-169-7			
REACH: 01-2119471299-27			
DISTILLATES (PETROLEUM),			
SOLVENT-DEWAXED HEAVY			
PARAFFINIC			

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version 7.1 (14-09-2015) - Page 2/8		
FORK OIL EXP M 10W 6x1L - 105930		
CAS: 112-90-3	GHS07 GHS05 GHS09 GHS08	0 <- x % < 1

CAS: 112-90-3	GHS07, GHS05, GHS09, GHS08	0 <= x % < 1
EC: 204-015-5	Dgr	
	Acute Tox. 4, H302	
(Z)-OCTADEC-9-ENYLAMINE	Asp. Tox. 1, H304	
	Skin Corr. 1B, H314	
	STOT SE 3, H335	
	STOT RE 2, H373	
	Aquatic Acute 1, H400	
	M Acute = 10	
	Aquatic Chronic 1, H410	
	M Chronic = 10	
CAS: 128-39-2	GHS07, GHS09	0 <= x % < 1
EC: 204-884-0	Wng	
REACH: 01-2119490822-33	Skin Irrit. 2, H315	
	Aquatic Acute 1, H400	
2,6-DI-TERT-BUTYLPHENOL	M Acute = 1	
	Aquatic Chronic 1, H410	
	M Chronic = 1	
CAS: 40027-38-1	GHS07, GHS05, GHS09	0 <= x % < 1
EC: 254-754-2	Dgr	
	Acute Tox. 4, H302	
L'ACIDE OLÉIQUE, COMPOSÉ DE	Skin Corr. 1C, H314	
(Z)-N-OCTADÉC-9-ENYLPROPANE-1,3	Aquatic Acute 1, H400	
-DIAMINE	M Acute = 1	

Information on ingredients :

Note L: The carcinogen classification does not apply because the substance contains less than 3 % w/w of dimethyl sulphoxide (DMSO) measured using the IP 346 method.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

Remove the victim to fresh air. If the symptoms persist, call a physician.

In the event of splashes or contact with eyes :

Wash immediately and abundantly with water, including under the eyelids.

In the event of splashes or contact with skin :

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

Dry agent, foam, carbon dioxide.

Unsuitable methods of extinction

High volume water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health. Do not breathe in smoke.

In the event of a fire, the following may be formed : - carbon monoxide (CO)

- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8. Spilled product may make surfaces slippery.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Avoid contact with eyes.

Fire prevention :

Prevent access by unauthorised personnel.

Take precautionary measures against static discharges by bonding and grounding equipment. No smoking.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Ensure good ventilation at the workplace

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Do not breathe fumes, vapour, spray.

7.2. Conditions for safe storage, including any incompatibilities

Store between 5°C and 40°C in a dry, well ventilated place. Only use hydrocarbon-resistant containers, joints and pipes. Storage limit 36 months

Storage

Keep out of reach of children.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2) **Final use:** Exposure method:

Potential health effects: DNEL : Workers. Dermal contact. Long term systemic effects. 2.77 mg/kg de poids corporel/jour

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) FORK OIL EXP M 10W 6x1L - 105930

Exposure method: Potential health effects: DNEL :

Final use: Exposure method: Potential health effects:

DNEL :

Exposure method: Potential health effects: DNEL :

Final use: Exposure method: Potential health effects: DNEL :

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3) **Final use:** Exposure method: Potential health effects: DMEL :

Predicted no effect concentration (PNEC):

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2) Environmental compartment: PNEC :

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3) Environmental compartment: PNEC :

Environmental compartment: PNEC :

Environmental compartment: PNEC :

Environmental compartment: PNEC :

Environmental compartment: PNEC : Inhalation. Long term systemic effects. 19.6 mg de substance/m3

Consumers. Dermal contact. Long term systemic effects. 2.77 mg/kg de poids corporel/jour

Inhalation. Long term systemic effects. 19.6 mg de substance/m3

Man exposed via the environment. Inhalation. Long term systemic effects. 5.8 mg de substance/m3

Workers. Inhalation. Long term local effects. 0.38 mg de substance/m3

Soil. 38.9 µg/kg

Fresh water. 0.45 µg/l

Sea water. 0.045 µg/l

Intermittent waste water. 4.5 µg/l

Fresh water sediment. 0.196 mg/kg

Marine sediment. 0.0196 mg/kg

Waste water treatment plant. 10 mg/l

Soil. 10 mg/kg

Fresh water. 0.00026 mg/l

Sea water. 0.00026 mg/l

Intermittent waste water. 0.55 mg/l

Fresh water sediment. 0.1794 mg/kg

Environmental compartment:	Marine sediment.
PNEC :	0.01794 mg/kg

8.2. Exposure controls

Suitable technical inspections

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.

Personnel shall wear regularly laundered overalls.

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Breathing apparatus only when aerosol or spray are formed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Fluid liquid.	
Color:	brown	
Important health, safety and environmental information		
pH :	Not relevant.	
Flash Point Interval :	PE > 100°C.	
Vapour pressure (50°C) :	Not relevant.	
Density :	<1	
Water solubility :	Insoluble.	
Viscosity :	35.2 mm²/s à 40°C	

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from heat and from sources of ignition

10.5. Incompatible materials

Strong oxidants

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

ECTION 11 : TOXICOLOGICAL INFORMATION	
11.1. Information on toxicological effects	
No data available.	
11.1.1. Substances	
Acute toxicity :	
L'ACIDE OLÉIQUE, COMPOSÉ DE (Z)-N-OCTADÉ Oral route :	C-9-ENYLPROPANE-1,3-DIAMINE (CAS: 40027-38-1) 300 < LD50 <= 2000 mg/kg Species : Rat OCDE Ligne directrice 423 (Toxicité aiguë par voie orale - Méthode de la classe de toxicité aiguë)
2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)	
Oral route :	LD50 > 5000 mg/kg Species : Rat
Dermal route :	LD50 > 5000 mg/kg Species : Rabbit
(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)	
Oral route :	300 < LD50 <= 2000 mg/kg Species : Rat
Skin corrosion/skin irritation :	
L'ACIDE OLÉIQUE, COMPOSÉ DE (Z)-N-OCTADÉ	C-9-ENYLPROPANE-1,3-DIAMINE (CAS: 40027-38-1)
Corrosivity :	Causes severe skin burns.
11.1.2. Mixture	
Skin corrosion/skin irritation :	
"Repeated or prolonged exposure may cause skin irri	itation and dermatitis, due to degreasing properties to the product."
Serious damage to eyes/eye irritation :	
Mild eye irritation	
Aspiration hazard :	
"Inhalation of vapours may cause irritation of the resp	piratory system in very susceptible persons."

"Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons." May cause lung damage if swallowed

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

L'ACIDE OLÉIQUE, COMPOSÉ DE (Z)-N-OCTADÉC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 40027-38-1)

Crustacean toxicity :	EC50 > 0.01 mg/l
	Species : Daphnia sp.
	Duration of exposure : 48 h
	OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)
(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)	
Fish toxicity :	0.01 < LC50 <= 0.1 mg/l
	Factor M = 10
	Species : Pimephales promelas
	OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)
Crustacean toxicity :	0.01 < EC50 <= 0.1 mg/l
	Factor $M = 10$
	Species : Daphnia magna
	OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity :	0.01 < ECr50 <= 0.1 mg/l
	Factor M = 10
	Species : Desmodesmus subspicatus
2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)	
Fish toxicity :	LC50 >= 1.4 mg/l
	Duration of exposure : 96 h
	NOEC = 0.43 mg/l
	Duration of exposure : 14 jours
Crustacean toxicity :	EC50 = 0.45 mg/l
	Species : Daphnia magna
	Duration of exposure : 48 h
Algae toxicity :	ECr50 = 1.2 mg/l
	Duration of exposure : 72 h
12.1.2. Mixtures	
12.1.2. MIALUIES	
Fish toxicity : H	armful.
	10 < LC50 <= 100 mg/l
12.2. Persistence and degradability	
12.2.1. Substances	
	-9-ENYLPROPANE-1,3-DIAMINE (CAS: 40027-38-1)
Biodegradability :	Rapidly degradable.
2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)	
Biodegradability :	no degradability data is available, the substance is considered as not
	degrading quickly.
(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)	
Biodegradability :	Rapidly degradable.
12.3. Bioaccumulative potential	
12.3.1. Substances	
(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)	
Bioaccumulation :	BCF >= 500.
12.4. Mobility in soil	
Not very mobile in soil.	
The product is insoluble in water and will spread on the	e surface
12.5. Results of PBT and vPvB assessment	
No data available.	
12.6. Other adverse effects	
Do not dispose of the product in the natural environme	nt, effluents or surface waters.
German regulations concerning the classification of	
WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous	for water.

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Fis

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.
- Container information:

No data available.

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws) : Hazardous for water.

15.2. Chemical safety assessment

No data available.

15.3 This substance is to be managed using the conditions specified in an applicable Group Standard HSR002606

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

DMEL : Derived Minimal Effect Level

- PNEC : Predicted No-Effect Concentration
- ADR : European agreement concerning the international carriage of dangerous goods by Road.
- IMDG : International Maritime Dangerous Goods.
- IATA : International Air Transport Association.
- ICAO : International Civil Aviation Organisation
- RID : Regulations concerning the International carriage of Dangerous goods by rail.
- WGK : Wassergefahrdungsklasse (Water Hazard Class).
- PBT: Persistent, bioaccumulable and toxic.
- vPvB : Very persistent, very bioaccumulable.
- SVHC : Substances of very high concern.